

Pom-Pom

- Ceramic tiles
- Gloss finish
- Suitable for internal wall applications

9
COLOURS

1
FINISH

1
TILE SIZE

GRESTEC.CO.UK / 0345 130 2241



IMO44954	IMO44955	IMO44956	IMO44957	IMO44958	IMO44959
IMO44960	IMO44961	IMO44962			
IMO44954T1	IMO44955T1	IMO44956T1	IMO44957T1	IMO44958T1	IMO44959T1
IMO44960T1	IMO44961T1	IMO44962T1			

	SIZE (MM)	THICKNESS	FINISHES
1	75x300	8MM	GLOSS

1

REQUEST SAMPLES, PRINT COLOURS MAY VARY.

FIND US ON:



TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Sizes	ISO 10545-2	Conforms
Water absorption	ISO 10545-3	>10%
Flexural resistance	ISO 10545-4	>17N/mm ²
Modulus of rupture	ISO 10545-4	Conforms
Linear expansion thermal coefficient	ISO 10545-8	<7x10 ⁻⁶ oC ⁻¹
Resistance to thermal shock	ISO 10545-9	Resistant
Crazing resistance	ISO 10545-11	Resistant
Resistance to chemical products	ISO 10545-13	Min GB
Stain resistance	ISO 10545-14	Min class 3

CLEANING + MAINTENANCE ADVICE

INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure. • Clean wall tiling with a dry cloth when joints are hard.

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Remove dust with a dry cloth • Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well