

# BENNET

- Industrial style
- Suitable for internal wall applications
- Glossy

6

COLOURS

1

FINISH

1

TILE SIZE

[www.grestec.co.uk](http://www.grestec.co.uk) | T: 0345 130 2241 | E: [sales@grestec.co.uk](mailto:sales@grestec.co.uk)



AAG44306  
LRV: 65



AAG44307  
LRV: 56



AAG44308  
LRV: 22



AAG44309  
LRV: 11



AAG44310  
LRV: 33

1



	SIZES (mm)	>  <	FINISHES
1	75x300	9.5mm	GLOSS

LRV VALUES VARY BATCH TO BATCH PLEASE CONTACT FOR ADVICE. PRINT COLOURS MAY VARY, PLEASE REQUEST SAMPLES.

FIND US ON:    





LRV VALUES VARY BATCH TO BATCH PLEASE CONTACT FOR ADVICE. PRINT COLOURS MAY VARY, PLEASE REQUEST SAMPLES.

FIND US ON:    



## TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Sizes	ISO 10545-2	Conforms
Water absorption	ISO 10545-3	>10%
Breaking of rupture	ISO 10545-4	>15N/mm <sup>2</sup>
Resistance to chemical products	ISO 10545-13	GA
Resistance to stains	ISO 10545-13	Class 5

## CLEANING + MAINTENANCE ADVICE

### INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul style="list-style-type: none"> <li>• Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure.</li> <li>• Clean wall tiling with a dry cloth when joints are hard.</li> </ul>

### ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> <li>• Remove dust with a dry cloth</li> <li>• Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well</li> </ul>