





Inspired by marble and reproduced using the most advanced porcelain tile technology. Calke Marble is suitable for a range of applications, thanks to the hard-wearing qualities of porcelain. From polished to satin and chiselled finishes, Calke is ideal for both residential and commercial spaces.











9mm thick



TMRM46215 LRV: 63



TMRM32151 *LRV: 42*

10mm thick



TMRM43899HON *LRV: 59*







Formats

	Sizes (mm)	> <	TMRM46215SAT	TMRM46215POL	TMRM32151	TMRM32151POL	TMRM32151SAT	TMRM43899HON
1	1200x2800	6mm						
2	1200x2600	6mm				9	1	
3	1200x1200	6mm				9	9	
4	600x1200	6mm						
5	600x1200	9-10mm			1	9		
6	600x600	9-10mm			1	97		
7	300x600	9-10mm			7	97		
8	300x300	9-10mm			1	1		
9	150x150	9-10mm			1	9		
10	50x50 MOS ON 300x300 MESH	9-10mm				1		
11	SK 50x600	9mm						
12	ST 300x600 *	9mm				P		

Slip rating: Nat (R10) | Polished (-) | Satin (-) | Honed (-)



Above Wall: TMRM43899HON

Right

Wall: TMRM46215





Above

Wall: TMRM32152POL



Technical data sheet - ISO 10545 average values

2	Sizes	Conforms
3	Water absorption	Conforms
4	Bending strength	Conforms
6	Deep abrasion resistance	<150mm³ Natural
8	Coefficient of linear thermal expansion	<9MK-1
9	Thermal shock resistance	Resistant
12	Frost resistance	Frost proof
14	Stain resistance	Class 5
	Slip resistance	NAT R10

Sustainability information







Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly. Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.