

DELOS

- Expansive range of colours
- Suitable for wall + floor applications
- Frost-proof

22
COLOURS


1
FINISH

1
TILE SIZE

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk



CIM34907 LRV: 63	CIM34981 LRV: 47	CIM34982 LRV: 19	CIM34924 LRV: 6	CIM34984 LRV: 11	CIM34910 LRV: 22	CIM34983 LRV: 48	CIM34921 LRV: 30
CIM34914	CIM34986	CIM34987 LRV: 13	CIM34913	CIM34909 LRV: 32	CIM34985	CIM34917 LRV: 23	CIM34911 LRV: 45
CIM34915	CIM34979	CIM34980 LRV: 23	CIM34923 LRV: 7	CIM34920	CIM34908 LRV: 41		



	SIZES (mm)	> <	FINISH
1	25x25 mosaics on 300x300 mesh-back sheet	3.5mm	NAT (R10/C)

PRINT COLOURS MAY VARY, PLEASE REQUEST SAMPLES. LRV VALUES CAN VARY BATCH TO BATCH, PLEASE CONTACT FOR ADVICE.



TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Water absorption	ISO 10545-3	<0.5%
Sizes	ISO 10545-2	10% : Thickness 0.75%: Rectangularity 1%: Straightness
Breaking strength	ISO 10545-4	1100-2200N/mm ²
Deep abrasion resistance	ISO 10545-7	140 mm ³
Coefficient of linear thermal expansion	ISO 10545-8	6.9x7.0x10 ⁻⁶ °C ⁻¹
Resistance to thermal shock	ISO 10545-9	Conforms
Frost resistance	ISO 10545-12	Conforms
Resistance to chemical products	ISO 10545-13	ULA
Slip resistance (Shod)	DIN 51130	Natural - R10/C
Stain resistance	ISO 10545-14	Class 3

CLEANING + MAINTENANCE ADVICE**INITIAL WASHING**

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product	Deterdek (1:5 diluted in water)
Coverage	Deterdek (5 l per 100m ²)
Equipment	Single-disc professional floor cleaner, liquid vacuum cleaner and cloth
Procedure	<ul style="list-style-type: none"> • After the floor is swept and soaked with water, spread the diluted Deterdek onto the floor. • Then scour with single-disc professional cleaner • Vacuum the residue, rinse the floor well and then mop with a liquid vacuum cleaner or a cloth.

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth or mop (For large areas the use of a cleaning machine is recommended)
Procedure	<ul style="list-style-type: none"> • Dilute Filacleaner in warm water • Wipe a cloth wet with the solution over the floor • Rinse the floor in case of concentrated solutions of Filacleaner

SPECIAL MAINTENANCE

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product	Fila PS/87 (1:5 diluted in water)
Coverage	5 l per 100m ² (when diluted 1:5)
Procedure	<ul style="list-style-type: none"> • Dilute Fila PS/87 in 1:5 in water • Apply to the floor previously soaked with water and leave for a few minutes • Scrub with a single disc professional cleaner • Mop up residue with a liquid vacuum cleaner or cloth