

Material: **Porcelain** | Appearance: **Marble** | Application: **Walls and floors**

Calke Marble

Inspired by marble and reproduced using the most advanced porcelain tile technology. Calke Marble is suitable for a range of applications, thanks to the hard-wearing qualities of porcelain. From polished to satin and chiselled finishes, Calke is ideal for both residential and commercial spaces.




Shade variation: V3 - High



9mm thick



TMRM46215



TMRM32151
LRV: 42



TMRM32152
LRV: 9

10mm thick



TMRM43899HON



Calke TMRM43899HON



LRV and PTV values can vary batch to batch, please contact for advice.
Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:



Calke Marble



Formats

	Sizes (mm)	> <	TMRM46215SAT	TMRM46215POL	TMRM32151	TMRM32151POL	TMRM32151SAT	TMRM32152	TMRM32152POL	TMRM43899HON
1	1200x2800	6mm								
2	1200x2600	6mm								
3	1200x1200	6mm								
4	600x1200	6mm								
5	600x1200	9-10mm								
6	600x600	9-10mm								
7	300x600	9-10mm								
8	73x83 HEX on 285x335 MESH	9.5mm								
9	300x300	9-10mm								
10	150x150	9-10mm								
11	50x50 MOS ON 300x300 MESH	9-10mm								
12	SK 50x600	9mm								
13	ST 300x600 *	9mm								

Slip rating: Nat (R10) | Polished (-) | Satin (-) | Honed (-)

Material: **Porcelain** | Appearance: **Marble** | Application: **Walls and floors**



Calke Marble



Above
Wall: TMRM43899HON




Right
Wall: TMRM46215



Above
Wall: TMRM32152POL

LRV and PTV values can vary batch to batch, please contact for advice.
Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:    



Calke Marble

Technical data sheet - ISO 10545 average values

2	Sizes	Conforms
3	Water absorption	Conforms
4	Bending strength	Conforms
6	Deep abrasion resistance	<150mm ³ Natural
8	Coefficient of linear thermal expansion	<9MK-1
9	Thermal shock resistance	Resistant
12	Frost resistance	Frost proof
14	Stain resistance	Class 5
	Slip resistance	NAT R10

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.