

Material: **Ceramic** | Appearance: **Handcrafted** | Application: **Walls**

9
Colours

2
Finishes

4
Tile sizes

Ewell

Ewell offers a delicate monochrome palette which, through a perfect balancing of tone, brightness and colour intensity, creates a uniform, harmonious effect. Ewell is suitable for internal wall applications.



Shade variation: V2 - moderate



Gloss



QTG39100
LRV: 73



QTG39163



QTG39164



QTG39103
LRV: 0



QTG39167



QTG39166



QTG39102
LRV: 53




QTG39162

Matt



QTG39108
LRV: 82

SIZES (mm)		> <	QTG39100	QTG39163	QTG39164	QTG39103	QTG39167	QTG39166	QTG39102	QTG39162	QTG39108
1	132x400	9mm	<input type="checkbox"/>								<input type="checkbox"/>
2	65x400	9mm	<input type="checkbox"/>	<input type="checkbox"/>							<input type="checkbox"/>
3	65x266	9mm	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
4	65x132	9mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
5	65x266 BULLNOSE LINEARE	9mm	<input type="checkbox"/>								
6	12x266 JOLLY	9mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	



Seki BMCC52131



LRV and PTV values can vary batch to batch, please contact for advice. Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:



Ewell



Above
Ewell

Right
Ewell QTG39103 QTG39111



Above
Ewell QTG39100 QTG39101 QTG39102

LRV and PTV values can vary batch to batch, please contact for advice.
Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:



Ewell

Technical data sheet - ISO 10545 average values

2	Sizes	Conforms
3	Water absorption	Conforms
4	Bending strength	Conforms
9	Thermal shock resistance	Resistant
11	Crazing resistance	Resistant
12	Frost resistance	Resistant
14	Stain resistance	Class 5

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.
Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.
Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.
Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.