

Material: **Porcelain** | Appearance: **Stone** | Application: **Walls and floors**

3

Colours

1

Finish

11

Tile size

Farrell

Three marble effect colours, characterised by scratches, aging, and imperfections, but whose modern colours bring out a contemporary look; suitable for commercial and residential areas. Farrell was designed for both those who seek a more classic look and those who prefer a more minimalist style.



V2-V3 shade variation



Mix decors



TMMO43848
LRV: 66




TMMO43849
LRV: 59



TMMO43850
LRV: 39




TMMO43859RHOM



TMMO43859

	Sizes (mm)	> <	Finishes
1	600x1200	9.5mm	NAT (R10) / ≥36 PTV
2	800x800	11mm	NAT (R10) / ≥36 PTV
3	600x600	9.5mm	NAT (R10) / ≥36 PTV
4	300x600	9.5mm	NAT (R10) / ≥36 PTV
5	100x600 MIX ALL COLOURS	9.5mm	NAT (R10) / ≥36 PTV
6	300x300	9.5mm	NAT (R10) / ≥36 PTV
7	150x150	9.5mm	NAT (R10) / ≥36 PTV
8	75x150	9.5mm	NAT (R10) / ≥36 PTV
9	50x50 MOS on 300x300 MESH	9.5mm	NAT (R10) / ≥36 PTV
10	75x102 RHOM on 309x309 MESH	9.5mm	NAT (R10) / ≥36 PTV
11	73x83 HEX on 285x335 MESH	9.5mm	NAT (R10) / ≥36 PTV
12	ST 330x1200x40	9.5mm	NAT (R10) / ≥36 PTV
13	SK 70x600	9.5mm	NAT (R10) / ≥36 PTV



LRV and PTV values can vary batch to batch, please contact for advice.
Swatch colours may vary, samples should be requested.



Material: **Porcelain** | Appearance: **Stone** | Application: **Walls and floors**



Farrell



Above
Floor: TMMO43850
Wall: TMMO43850CHEV

Right
Wall: TMMO43859RHOM



LRV and PTV values can vary batch to batch, please contact for advice.
Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:    



Farrell

Technical data sheet - ISO 10545 average values

2	Sizes	Conforms
3	Water absorption	Conforms
4	Breaking of rupture Modulus of rupture	Conforms Conforms
6	Resistance to deep abrasion	Resistant
8	Linear thermal expansion	<9MK-1
9	Thermal shock resistance	Resistant
11	Crazing resistance	<150mm3
12	Frost resistance	Resistant
13	Chemical resistance	UHA to UHB
14	Stain resistance	Class 5
	Slip resistance	NAT - R10, ≥36 PTV
	Shade variation	V2 Moderate - TMMO43848 + TMMO43849 V3 High - TMMO43850

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.