SIMPLEX PICCOLO

- Matt + gloss finish in some coloursSuitable for wall applications
- Part of the Simplex Shades range
- Contains at least 40% recycled material







www.grestec.co.uk | T: +44 (0) 345 130 2241 | E: sales@grestec.co.uk





GLOSS













TTB30362









TTB30363


TTB30364

TTB30380

TTB30365

TTB30366

TTB30382



	SIZE (mm)	> <	TTB30362	TTB30380	TTB30381	TTB30382	TTB30381	TTB30382	TTB30363	TTB30364	TTB30365	TTB30366
1	75x300	8mm										
2	75x150	8mm										
3	75x150 BEV	8.5mm										





















TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES		
Water absorption	ISO 10545-3	AA >10% GRUPPO BIII		
Bending Strength	ISO 10545-4	RM>150Kg/cm2		
Crazing resistance	ISO 10645-11	Resistant		
Resistance to chemical products	ISO 10545-13	Conforms		
Stain resistance	ISO 10545-14	Conforms		
Scratch Hardness	EN 101	Hardness 4 (Gloss)		
SCI altii Hai uiiess	EN IUI	Hardness 5 (Matt)		

SUSTAINABILITY INFORMATION



MATERIAL	RECYCLED CONTENT			
Ceramic tiles	At least 40%			



CLEANING + MAINTENANCE ADVICE

INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	 Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure. Clean wall tiling with a dry cloth when joints are hard.

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)			
Equipment	Cloth			
Procedure	 Remove dust with a dry cloth Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well 			



