

Simplex Piccolo




- Matt + gloss finish in some colours
- Suitable for wall applications
- Part of the Simplex Shades range

GRESTEC.CO.UK / 0345 130 2241



GLOSS

MATT



TTB30362

TTB30380

TTB30381

TTB30382

TTB30363

TTB30364

TTB30365

TTB30366



	SIZE (MM)	THICKNESS	FINISHES		TTB30362	TTB30380	TTB30381	TTB30382	TTB30363	TTB30364	TTB30365	TTB30366
1	75x300	8MM	-	GLOSS	■	■	■	■				
2	75x150	8MM	MATT	GLOSS	■				■	■	■	■

FIND US ON:



REQUEST SAMPLES, PRINT COLOURS MAY VARY.



TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Water absorption	ISO 10545-3	AA >10% GRUPPO BIII
Bending Strength	ISO 10545-4	RM>150Kg/cm2
Crazing resistance	ISO 10645-11	Resistant
Resistance to chemical products	ISO 10545-13	Conforms
Stain resistance	ISO 10545-14	Conforms
Scratch Hardness	EN 101	Hardness 4 (Gloss) Hardness 5 (Matt)

CLEANING + MAINTENANCE ADVICE**INITIAL WASHING**

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure. • Polish wall tiling with a dry cloth when joints are hard.

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Remove dust with a dry cloth • Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well