

Symmetry

- Hexagon tiles
- Suitable for internal wall applications

7
COLOURS

2
FINISHES

1
TILE SIZE


GRESTEC.CO.UK / 0345 130 2241



MATT



GLOSS



	SIZE (MM)	THICKNESS	FINISHES	
1	175x200 HEX	8.5MM	GLOSS	MATT

LRV VALUES CAN VARY BATCH TO BATCH, PLEASE CONTACT FOR SPECIFIC ADVICE. SWATCH COLOURS MAY VARY, SAMPLES SHOULD BE REQUESTED.

FIND US ON:



TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Water absorption	ISO 10545-3	<3% BI
Breaking strength	ISO 10545-4	>1100N
Resistance to Abrasion	ISO 10545-7	1
Resistance to thermal shock	ISO 10545-9	Resistant
Crazing resistance	ISO 10545-11	Resistant
Frost Resistant	ISO 10545-12	Resistant
Resistance to chemical products	ISO 10545-13	Resistant
Resistance to stains	SO 10545-14	Class 5
Scratch Hardness (MOHS)	EN 101	4

CLEANING + MAINTENANCE ADVICE

INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure. • Clean wall tiling with a dry cloth when joints are hard.

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Remove dust with a dry cloth • Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well

LRV VALUES VARY BATCH TO BATCH PLEASE CONTACT FOR ADVICE. PRINT COLOURS MAY VARY, PLEASE REQUEST SAMPLES.

FIND US ON:    

