

# LULWORTH

5

COLOURS

3

FINISH

6

TILE SIZE

Stone effect porcelain suitable for internal and external applications. Available in 10 and 20mm thicknesses.



V2 moderate shade variation



10.5mm THICK


20mm THICK (R11/C) 600x900 ONLY




WED37804



WED37806




WED37805




WED37807




WED37808




WED37806THK



WED37805THK



WED37807THK



WED37808THK



	SIZE (mm)	>  <	FINISHES			WED37804	WED37805	WED37806	WED37807	WED37808
1	600x900	10.5mm	NAT (R10)	LAP	STR (R11/C)					
2	600x900 THK	20mm	-	-	THK (R11/C)					
3	600x600 *	10.5mm	NAT (R10)	LAP	STR (R11/C)					
4	300x600 *	10.5mm	NAT (R10)	LAP	-					
5	98x98 HEX on 300x300	10.5mm	NAT (R10)	-	-					
6	25x25 MOS on 300x300	10.5mm	NAT (R10)	-	-					
7	300x600/300x1200 STEPTREAD	10.5mm	-	-	STR (R11/C)					
8	300x600/300x900/300x1200 LIN	10.5mm	NAT (R10)	-	-					
9	300x600/300x900/300x1200 ANG	10.5mm	NAT (R10)	-	-					
10	75x600/ 65x1200 SKIRTING	10.5mm	NAT	-	-					

\*ALSO AVAILABLE NON-RECTIFIED

## TECHNICAL DATA SHEET - ISO 10545 AVERAGE VALUES

3	Water absorption	>0.5 %	13	Chemical resistance	Unaffected
4	Bending strength	Conforms		Slip resistance DIN 51130/ DIN 51097	NAT R10
12	Frost resistance	Frost-proof			

## SUSTAINABILITY INFORMATION



## CLEANING + MAINTENANCE ADVICE

### INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

**Product: Deterdek Pro**

### ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

**Product: CleanerPo**

### SPECIAL MAINTENANCE

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

**Product: PS/87 Pro**

*Please see [www.filasolutions.com](http://www.filasolutions.com) for methods of use, dilution and coverage.*

