

# PULLEN

- Suitable for internal wall applications
- Crackle effect
- V4- High shade variation
- EPD verified

6

COLOURS

1

FINISH

2

TILE SIZES

www.grestec.co.uk | T: +44 (0) 345 130 2241 | E: sales@grestec.co.uk



AAD44300



AAD44301



AAD44302




AAD44303



AAD44304



AAD44305




	SIZES (mm)	>  <	FINISHES
1	155x170 FISH SCALE (T1)	9.5mm	CRACKLE EFFECT
2	75x300	9.5mm	CRACKLE EFFECT

PRINT COLOURS MAY VARY, PLEASE REQUEST SAMPLES. FIND US ON:





## TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Sizes	ISO 10545-2	Conforms
Water absorption	ISO 10545-3	>10%
Flexion resistance	ISO 10545-4	>12N/mm <sup>2</sup>
Thermal shock resistance	ISO 10545-9	Resistant
Crazing resistance	ISO 10545-11	Resistant
Resistance to chemical products	ISO 10545-13	GA
Resistance to stains	ISO 10545-13	Class 5
Shade variation	-	 V4 - High shade variation

## SUSTAINABILITY INFORMATION

MATERIAL	EPD
Ceramic tiles	Yes



## CLEANING + MAINTENANCE ADVICE

### BEFORE GROUTING

A pre grout protector Fila PRW200 is advised to protect the tiles; this is a temporary seal that when cleaning the grout will wash off.

### INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product	Filacleaner (Diluted 1:10 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> <li>• Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure.</li> <li>• Clean off wall tiling with a dry cloth when joints are hard.</li> </ul>

### IMPREGNATING

It is also recommended to seal the body of the tiles with Fila MP90.

### ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:5 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> <li>• Remove dust with a dry cloth</li> <li>• Dilute Filacleaner in warm water</li> <li>• Regularly soak cloth wet with the solution and wring out well before covering tiles.</li> </ul>