

Rustic Two

- Expansive range of colours
- Handmade effect
- Suitable for internal wall applications

12
COLOURS

1
FINISH

1
TILE SIZES

GRESTEC.CO.UK / 0345 130 2241



RAR42404
LRV: 67



RAR42405
LRV: 64



RAR42406
LRV: 44



RAR42407
LRV: 45



RAR42408
LRV: 70



RAR42409
LRV: 36



RAR42410
LRV: 19



RAR42411
LRV: 51



RAR42412
LRV: 46



RAR42413
LRV: 16



RAR42414
LRV: 8



RAR42415
LRV: 29

1



2



	SIZE (MM)	THICKNESS	FINISHES
1	100x100	8.5MM	GLAZED
2	15x200 MATITA	8.5MM	GLAZED

LRV VALUES VARY BATCH TO BATCH PLEASE CONTACT FOR ADVICE. PRINT COLOURS MAY VARY, PLEASE REQUEST SAMPLES.

FIND US ON:



TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Water absorption	ISO 10545-3	0.5%
Breaking strength	ISO 10545-4	>1300N
Resistance to thermal shock	ISO 10545-9	Conforms
Frost resistance	ISO 10545-12	Conforms

CLEANING + MAINTENANCE ADVICE

INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure. • Clean wall tiling with a dry cloth when joints are hard.

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Remove dust with a dry cloth • Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well