


# GIBRALTAR

- Suitable for internal wall applications
- Handmade effect
- Crackle glaze
- Contains 55% recycled material and EPD verified 

8

COLOURS


1

FINISH

3

TILE SIZES

www.grestec.co.uk | T: +44 (0) 345 130 2241 | E: sales@grestec.co.uk



ADN32503  
LRV: 68



ADN32505  
LRV: 34



ADN32507  
LRV: 10



ADN32527  
LRV: 44



ADN32526  
LRV: 47



ADN32504  
LRV: 65



ADN32528  
LRV: 44



ADN32506  
LRV: 22



	SIZES (mm)	>  <	FINISHES	ADN32503	ADN32505	ADN32507	ADN32527	ADN32526	ADN32504	ADN32528	ADN32506
1	75x300	9mm	CRACKLE GLAZE								
2	150x150	9mm	CRACKLE GLAZE								
3	75x150	9mm	CRACKLE GLAZE								
4	130x150 RODAPIE	9mm	CRACKLE GLAZE								
5	75x150 CORNISA	9mm	CRACKLE GLAZE								
6	75x150 HOJAS	9mm	CRACKLE GLAZE								
7	50x150 MOLDURA	9mm	CRACKLE GLAZE								
8	25x150 BARRA	9MM	CRACKLE GLAZE								

LRV VALUES VARY BATCH TO BATCH, CONTACT US FOR FURTHER ADVICE.

SWATCH COLOURS MAY VARY, SAMPLES SHOULD BE REQUESTED. FIND US ON:    





## TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Water absorption	ISO 10545-3	> 10% Group BLL
Bending strength	ISO 10545-4	RM > 150 kg/cm <sup>2</sup>
Resistance to chemical products	ISO 10545-13	Resistant
Stain resistance	ISO 10545-14	Resistant
Crazing resistance	ISO 10545-11	Resistant
Scratch hardness (MOHS scale)	EN 101	Gloss - hardness 4

## SUSTAINABILITY INFORMATION

MATERIAL	RECYCLED CONTENT	EPD	ISO 14001:2015 – ENVIRONMENTAL MANAGEMENT
Glazed porcelain tiles	55%	Yes	Yes



## CLEANING + MAINTENANCE ADVICE

### INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul style="list-style-type: none"> <li>• Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure.</li> <li>• Clean wall tiling with a dry cloth when joints are hard.</li> </ul>

### ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> <li>• Remove dust with a dry cloth</li> <li>• Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well</li> </ul>