NEWARK







Newark presents a collection of full body porcelain tiles inspired by concrete. Available in several sizes, square and rectangular, in five concrete shades.













Shade variation- V2 moderate














IMF37172

IMF37173

IMF37174

IMF37175

IMF37171



	SIZES (mm)	> <	FINI	FINISHES	
1	900x900	10.5mm	NAT (R10)	-	
2	450x900	10.5mm	NAT (R10)	-	
3	600x600	10.5mm	NAT (R10)	STR (R11/B)	
4	300x600	10.5mm	NAT (R10)	STR (R11/B)	
5	600x600 LOS	10.5mm	NAT (R10)	-	
6	450x450	10.5mm	NAT (R10)	-	
7	50x50 MOS on 300x300 MESH	10.5mm	NAT (R10)	-	
8	250x300 HEX MOS	10.5mm	NAT (R10)	-	



TECHNICAL DATA SHEET - ISO 10545 AVERAGE VALUES

2	Dimension and surface quality	Conforms	9	Thermal shock resistance	Resistant
3	Water absorption	0.05%	13	Chemical resistance	Min UB
4	Flexural resistance	50N/mm ²		Slip resistance	NAT: R10 STR: R11/B
6	Deep abrasion resistance	140mm³		Stain resistance	Min. 3
8	Coefficient of linear thermal expansion	<7x10-6oC-1		Stann esistance	

SUSTAINABILITY INFORMATION







CLEANING + MAINTENANCE ADVICE

INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime. **Product: Deterdek Pro**

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

SPECIAL MAINTENANCE

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.

