

# PIETRA DI REALE



Five neutral stone surfaces suitable for both indoor and outdoor in commercial and residential areas. Available in two finishes: natural and external 20mm thick.



V3 high shade variation



PIETRA DI REALE PGR33474



PIETRA DI REALE PGR33476



PIETRA DI REALE PGR33478



PGR33474  
LRV 57



PGR33475  
LRV 29



PGR33476  
LRV 7



PGR33477  
LRV 62



PGR33478  
LRV 16



	SIZES (mm)	>  <	FINISHES	PGR33474	PGR33475	PGR33476	PGR33477	PGR33478
1	750x1500	6mm	NAT (R10)	-				
2	600x1200 THK	20mm	-	THK (R11/C)				
3	600x1200	8mm	NAT (R10)	-				
4	1000x1000 THK	20mm	-	THK (R11/C)				
5	1000x1000	6mm	NAT (R10)	-				
6	750x750	6mm	NAT (R10)	-				
7	375x750	6mm	NAT (R10)	-				
8	600x600 THK	20mm	-	THK (R11/C)				
9	600x600	8mm	NAT (R10)	THK (R11/C)				
10	300x600	8mm	NAT (R10)	-				
11	50x50 MOS on 300x300 MESH	6mm	NAT (R10)	-				
12	375x1500 / 300x1000 / 300x1200 / 300x600 / 375x750 ST	8mm	NAT (R10)	-				
13	65x1000 / 65x750 / 70x600 SK	-	NAT (R10)	-				

LRV and PTV values can vary batch to batch, please contact for advice.  
Swatch colours may vary, samples should be requested.

Find us on:



www.grestec.co.uk | T: +44 (0)345 130 2241 | E: sales@grestec.co.uk



## LONDON STUDIOS

Grestec has its own Tile Studios in London where architects and designers can visit to discover the latest tile ranges and concepts.

Full of new and existing collections suitable for all situations; commercial, retail and residential. Our studio spaces are an excellent environment for ideas, solutions and project discussions, with plentiful samples to take away immediately or simply order for next day delivery. Further details can be found on our website.

**STUDIO 329 (APPOINTMENT ONLY)**  
Business Design Centre, 52 Upper Street,  
Islington, London, N1 0QH

**POP-UP STUDIO (UNMANNED/ WALK-INS)**  
The Building Centre, 26 Store Street,  
London, WC1E 7BT



## TECHNICAL DATA SHEET - ISO 10545 AVERAGE VALUES

2	Sizes	Length + width +/- 0.2% Thickness +/- 5.0% Linearity +/- 0.2% Wedging +/- 0.2% Warpage +/- 0.2%	12	Frost resistance	Resistant
3	Water absorption	<0.05%	13	Chemical resistance	UNAFFECTED
4	Bending strength	>42N/mm <sup>2</sup>		Slip resistance	NAT R10 THK R11
8	Coefficient of linear thermal expansion	7 MK-1			
9	Thermal shock resistance	Resistant			

## SUSTAINABILITY INFORMATION



## CLEANING + MAINTENANCE ADVICE

## INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

**Product: Deterdek**

## ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

**Product: FilaCleaner**

## SPECIAL MAINTENANCE

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

**Product: Fila PS/87**

Please see [www.filasolutions.com](http://www.filasolutions.com) for methods of use, dilution and coverage.

