

Larissa

- Metro tiles
- Suitable for internal wall applications
- Pastel shades

10
COLOURS

2
FINISHES

3
TILE SIZES

GRESTEC.CO.UK / 0345 130 2241



GLOSS



BMT31866 BMT31868 BMT31870 BMT31875 BMT31874 BMT31871 BMT31872 BMT31873 BMT31869

MATT




BMT31867

RANDOM MIX - 150x150



BMT31876

	SIZES (mm)	THICKNESS	BMT31868	BMT31871	BMT31872	BMT31873	BMT31869	BMT31870	BMT31874	BMT31875	BMT31866	BMT31867
1	250x400	7mm										
2	150x150	7mm										
3	75x150	7mm										



FIND US ON:    

REQUEST SAMPLES, PRINT COLOURS MAY VARY.



TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Water absorption	ISO 10545-3	15.1%
Breaking of rupture	ISO 10545-4	2N/mm ²
Crazing resistance	ISO 10545-11	Resistant
Resistance to chemical products	ISO 10545-13	GA
Resistance to stains	ISO 10545-13	Class 5- Stain removed

CLEANING + MAINTENANCE ADVICE

INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure. • Clean wall tiling with a dry cloth when joints are hard.

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Remove dust with a dry cloth • Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well