

ABAR

- Fan/ fishscale shape
- Supplied on mesh sheet
- Suitable for internal wall applications
- Crackle effect with glaze overlay

3
COLOURS


1
FINISH

1
TILE SIZE

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk




MAC45063



MAC45064



MAC45065



	SIZES (MM)	> <	FINISHES
1	82x93 FAN/ FISHSCALE on 294x302 MESH	7mm	GLOSS CRACKLE EFFECT

CLEANING + MAINTENANCE ADVICE

INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul style="list-style-type: none">• Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure.• Clean wall tiling with a dry cloth when joints are hard.

IMPREGNATING

It is also recommended to seal the body of the tiles with Fila MP90.

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none">• Remove dust with a dry cloth• Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well

***DUE TO THE GLAZE APPLIED TO THE TILE, SHARP SURFACE ABRASION MAY SCRATCH THE SURFACE**