


FLUX

- Metallic tiles
- Suitable for internal wall applications
- Gloss finish
- See Flux 2.0 for installed image on the right
- EPD verified 

4
COLOURS

1
FINISH

1
TILE SIZE

www.grestec.co.uk | T: +44 (0) 345 130 2241 | E: sales@grestec.co.uk



BEO46380



BEO46382



BEO46384



BEO46386

1



	SIZES (mm)	> <	FINISH
1	70x280	9mm	GLOSS

SWATCH COLOURS MAY VARY, SAMPLES SHOULD BE REQUESTED. FIND US ON:    

IMPORTANT INFORMATION - METALLIC EFFECT

The special metallic glaze of these tiles is particularly acid-sensitive therefore we recommend before grouting to apply a sealer on the tiles (e.g. Fila MP90) and wait to 1 or 2 days for setting up the possible 'crackle effect'.

Anti-limescale products should not be used for ordinary maintenance. We recommend to use a natural cleaner such as Fila Cleaner.

Do not use aggressive cleaning products such as bleach or ammonia.

Complaints due to a laying or fixing mistakes will not be accepted.

TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES	
Sizes	ISO 10545-2	Length and Width	±0,5
		Thickness	±0,5
		Straightness of Sides	<0,5%
		Surface Flatness	<0,5%
		Surface Quality	Perform
Water absorption	ISO 10545-3	Groupe I -> E ≤ 3%	
Breaking Strength	ISO 10545-4	≥ 600	
Modulus of Rupture	ISO 10545-4	≥ 30 N/mm ²	
Resistance to household chemicals and swimming pool salts	ISO 10545-13	Clean with water with neutral soap	

SUSTAINABILITY INFORMATION

MATERIAL	EPD
Ceramic tiles	Yes



CLEANING + MAINTENANCE ADVICE

INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure. • Clean wall tiling with a dry cloth when joints are hard.

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Remove dust with a dry cloth • Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well