

# VISTA ART

- Pattern tiles
- Suitable for wall applications
- Large format sizes

10  
COLOURS

1  
FINISH

1  
TILE SIZE


www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk



TSS46205



TSS46206




TSS46207



TSS46208




TSS46209



TSS46210




TSS46211



TSS46212



TSS46213



TSS46214



	SIZES (mm)	>  <	FINISHES
1	600x1200	6mm	MATT

SWATCH COLOURS MAY VARY, SAMPLES SHOULD BE REQUESTED. FIND US ON:    





**WARNINGS****RECOMMENDED APPLICATIONS**

Slabs decorated by using small-scale innovative production techniques, suitable for indoor wall cladding only. Small imperfections must be considered as a distinctive characteristic of the product, due to the production process. This innovative decorative technique improves definition and depth of colors, making surface abrasion less performing than conventional porcelain stoneware. For this reason, the instructions put on the catalogue and inside the packaging must be strictly followed.

**HANDLING**

When handling avoid contact with abrasive material and rubbing with other slabs or with the work surface. Do not leave utensils or other objects that can damage the surface on the slabs. The handling can be done by using specific frames with suction cups.

**CUTTING AND DRILLING**

Cuts and drillings must be executed with specific equipment starting from an incision in the back of the slabs. The worktop must be perfectly clean from dirt and debris that may damage the product.

**GENERAL INSTRUCTIONS**

Surface protection of the slab must be guaranteed during all stages of laying and grouting. We recommend to apply paper masking tape.

**GROUTING**

Only cement-based grouts are suitable and spatulas in plastic material, make sure all residues are removed before the grout hardens by using water and a non-abrasive sponge to avoid any damage to the surface of the slabs while cleaning it.

**DAILY MAINTENANCE**

Use neutral or water based detergents, and clean with a soft sponge or a microfiber cloth. Acid based limescale removers may be used, making sure to carefully rinse the surface with water after the application. Do not use solvents (alcohol or similar) and abrasive sponges.

**TECHNICAL SPECIFICATION**

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Sizes	ISO 10545-2	Conforms
Water absorption	ISO 10545-3	Conforms
Thermal shock resistance	ISO 10545-9	Resistant
Resistance to stains	ISO 10545-14	Class 3
Colour resistant to light	DIN 51130	Resistant