

Material: **Porcelain** | Appearance: **Stone** | Application: **Walls and floors**

# Calke Stone

Stone-enthused porcelain stoneware with an urban style. The technical properties of the 10 and 20mm thickness make Calke the ideal choice for styles that extend through indoor & outdoor areas.



Shade variation: V2 - moderate



9mm THK



TMRS43883  
LRV: 51



TMRS32149  
LRV: 46



TMRS43885  
LRV: 33

10mm THK



TMRS46228



LRV and PTV values can vary batch to batch, please contact for advice.  
Swatch colours may vary, samples should be requested.

[www.grestec.co.uk](http://www.grestec.co.uk) | T: 0345 130 2241 | E: [sales@grestec.co.uk](mailto:sales@grestec.co.uk)

Find us on:

4  
Colours

4  
Finishes

13  
Tile sizes



# Calke Stone



TMRS43883, TMRS43885

## Formats

Sizes (mm)		>  <	TMRS43883	TMRS43883THK	TMRS32149	TMRS32149BRU	TMRS32149COMB	TMRS32149THK	TMRS43885	TMRS43885THK	TMRS46228	TMRS46228THK	TMRS46228UM
1	1600x3200	12mm									■		
2	1200x2800	6mm									■		■
3	1200x2600	6mm							■				
4	1200x1200	6mm							■				
5	600x1200	9-10mm	■		■				■	■	■		
6	600x1200 THK	20mm		■				■				■	
7	800x800	9mm							■				
8	600x600	9-10mm	■		■	■	■		■		■		■
9	300x600	9-10mm	■		■	■	■		■		■		■
10	100x600 mix*	9mm			■								
11	300x300	9-10mm	■		■				■		■		
12	150x150	9-10mm	■		■				■		■		
13	50x50 MOS on 300x300	9mm	■		■	■	■		■				
14	73x83 HEX on 285x335	9mm			■								
15	50x600 SK	9mm	■		■				■				
16	300x600 ST**	9mm	■		■	■	■		■				

\*100x600 MIX: NAT, BRU and COMB

\*\*Steptread available on request

Material: **Porcelain** | Appearance: **Stone** | Application: **Walls and floors**



# Calke Stone



Above  
Wall: TMRS43885THK

Right  
Wall: TMRS43883



Above  
Wall: TMRS32149THK

LRV and PTV values can vary batch to batch, please contact for advice.  
Swatch colours may vary, samples should be requested.

[www.grestec.co.uk](http://www.grestec.co.uk) | T: 0345 130 2241 | E: [sales@grestec.co.uk](mailto:sales@grestec.co.uk)

Find us on:    



# Calke Stone

## Technical data sheet - ISO 10545 average values

2	Sizes	Conforms
3	Water absorption	Conforms
4	Bending strength	Conforms
6	Deep abrasion resistance	<150mm <sup>3</sup> (NAT + COMB)
8	Coefficient of linear thermal expansion	<9MK-1
9	Thermal shock resistance	Resistant
12	Frost resistance	Frost proof
14	Stain resistance	Class 5
	Slip resistance	NAT R10 COMB R10 THK R11

## Sustainability information



### Cleaning and maintenance advice

#### Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

#### Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

#### Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see [www.filasolutions.com](http://www.filasolutions.com) for methods of use, dilution and coverage.