


BARRANCO

- Soft pastel shades
- Gloss finish
- Handmade look
- EPD verified 



www.grestec.co.uk | T: +44 (0) 345 130 2241 | E: sales@grestec.co.uk



BEDG48315



BEDG48316



BEDG48317




BEDG48318



BEDG48319



BEDG48320



	SIZE (mm)	> <	FINISHES
1	65x200	9mm	GLOSS
2	200x200	9mm	GLOSS
3	15x200 JOLLY	9mm	GLOSS

SWATCH COLOURS MAY VARY, SAMPLES SHOULD BE REQUESTED. FIND US ON:    



TECHNICAL SPECIFICATION

TECHNICAL CHARACTERISTIC	STANDARD	AVERAGE VALUES
Water absorption	ISO 10545-3	1,6
Breaking charge N	ISO 10545-4	Conforms
Thickness \geq 7.5 mm	ISO 10545-4	Conforms
Flexion resistance N/mm ²	ISO 10545-4	Conforms
Abrasion resistance PEI Clase	ISO 10545-7	III
Resistance of Cracking	ISO 10545-11	Conforms
Frost Resistance	ISO 10545-12	Conforms
Thermal shock	ISO 10545-12	Conforms
Stain resistance	ISO 10545-14	Class 5
Resistance to chemical product	ISO 10545-13	a) Acids GLA b) Alkalis GHA c) Swimming Pool Salts GA

SUSTAINABILITY INFORMATION

MATERIAL	EPD
Ceramic tiles	Yes

**CLEANING + MAINTENANCE ADVICE****INITIAL WASHING**

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Clean off cement stains from grouting and other building work, which once hardened, will not be removed during any normal cleaning procedure. • Clean wall tiling with a dry cloth when joints are hard.

ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product	Filacleaner (Diluted 1:50 in warm water)
Equipment	Cloth
Procedure	<ul style="list-style-type: none"> • Remove dust with a dry cloth • Wash with FilaCleaner using a cloth that should be soaked often in the solution and wrung out well