


TILING IN DAMP ENVIRONMENTS AND SHOWERS ON WOODEN SUBSTRATES

- Guarantees the water protection of adjacent rooms
- Suitable for renovation work
- High level of chemical stability
- System with very low VOC emissions, improves the quality of air and increases the level of health protection for operators

SUBSTRATE

- 1 Timber panel on floor / Backer

PREPARATION OF SUBSTRATES




Keragrip Eco

Certified, eco-friendly, water-based adhesion promoter for compact, absorbent and non-absorbent substrates.

Coverage

≈ 0.1 – 0.2 kg/m²

WATERPROOFING




H40® Advanced

Rapid setting, multipurpose Gel-Adhesive, structural, flexible, thixotropic & fluid. For tiles and stone of all types and formats.

Coverage

Grey ≈ 1.3 kg/m² per mm of thickness
White ≈ 1.2 kg/m² per mm of thickness

- 4 Cement board




Nanodefense® Eco (1st coat)

Certified, eco-friendly, organic, water-based, mineral waterproofing product for absorbent substrates in damp environments.


Coverage

≈ 0.75 kg/m² per coat



Aquastop 120

Flexible NBR waterproof joint for perimeter and fractionizing joints in waterproofing systems. For use under ceramic and porcelain tiles and natural stone. Bonds directly on application.




Nanodefense® Eco (2nd coat)

Certified, eco-friendly, organic, water-based, mineral waterproofing product for absorbent substrates in damp environments.



TILE LAYING



H40® Gel

Standard setting, multipurpose Gel-Adhesive, structural, flexible, thixotropic & fluid. For tiles and stone of all types and formats.

Coverage

Grey ≈ 1.3 kg/m² per mm of thickness
White ≈ 1.2 kg/m² per mm of thickness


GROUTING



Fugalite® Bio

Water-based hypo-allergenic resin for waterproof, stain-proof, silk-effect grouting of porcelain tiles, natural stones and glass mosaic.

EXPANSION JOINTS



Silicone Color

Decorative sealant for tiles and mosaic in 50 design colours.
Green product for bio-building.