


TILING IN SWIMMING POOLS

- Ensures safe laying under continuous immersion
- It is not affected by aggressive water
- Increases the hygiene
- System with very low VOC emissions, improves the quality of air and increases the level of health protection for operators

WALL LEVELLING




Keralevel® Eco LR

Certified, fast-acting, eco-friendly, mineral levelling product for the high-performance, high-thickness correction of irregular substrates

Coverage

≈ 1.3 kg/m² per mm of thickness

WATERPROOFING




Aquastop Nanoflex® (1st coat) (2nd coat)

Certified, eco-friendly, breathable, anti-alkali and chlorine-resistant, mineral membrane for the flexible waterproofing with high levels of adhesion and durability of substrates before laying with adhesives. To be reinforced with Aquastop AR1, special reinforcing mesh made of alkali-resistant glass fibre.

Coverage

≈ 1.15 kg/m² per mm of thickness



Aquastop 120

Flexible NBR waterproof joint for perimeter and fractionizing joints in waterproofing systems. For use under ceramic and porcelain tiles and natural stone. Bonds directly on application.



Aquastop Nanosil

Eco-friendly rigid neutral silane sealant for waterproof sealing of hydraulic and electric systems, through elements and construction elements in pools and in Kerakoll® waterproofing systems.

Coverage ≈ 10 m (joint 5x5 mm) with 1 cartridge (290 ml)

TILE LAYING



H40® Gel

Standard setting, multipurpose Gel-Adhesive, structural, flexible, thixo & fluid. For tiles and stone of all types and formats.


Coverage

Grey ≈ 1.3 kg/m² per mm of thickness

White ≈ 1.2 kg/m² per mm of thickness




GROUTING



Fugalite® Bio

Water-based hypo-allergenic resin for waterproof, stain-proof, silk-effect grouting of porcelain tiles, natural stones and glass mosaic.

EXPANSION JOINTS



Silicone Color

Decorative sealant for tiles and mosaic in 50 design colours. Green product for bio-building.