


TILING TO EXISTING TILES AND NATURAL STONE

- Guarantees safe laying on existing floors and walls
- Ideal in renovation work
- Reduces operation times
- Avoids the costs and inconvenience of removal and disposal of the existing floor and wall tiles
- System with very low VOC emissions, improves the quality of air and increases the level of health protection for operators

SUBSTRATE

Before levelling and/or fixing, clean the old flooring thoroughly, making sure you eliminate all traces of dirt using specific cleaning products. If in doubt, sand the surface. Fix loose elements or elements that are not perfectly fixed, and fill in any gaps with specific product.

TILE LAYING ON WALL




H40® Gel

Standard setting, multipurpose gel-adhesive, structural, flexible, thixotropic & fluid. For tiles and stone of all types and formats.

Coverage

Grey ≈ 1.3 kg/m² per mm of thickness
White ≈ 1.2 kg/m² per mm of thickness

TILE LAYING ON FLOOR



Biogel® Revolution

Rapid setting, multi-purpose, flexible structural gel tile adhesive. Longer workability with accelerated adhesion for bonding even in extreme conditions of all types of material, on any substrate for any use. Eco-friendly.

Coverage

Grey ≈ 1.3 kg/m² per mm of thickness
White ≈ 1.2 kg/m² per mm of thickness


GROUTING



Fugabella® Color

Decorative Resina-cemento® (resin-cement) for grouting of ceramic and porcelain tiles, mosaic and natural stone in a 50-colour design range. Green product for bio-building.

EXPANSION JOINTS



Silicone Color

Decorative sealant for tiles and mosaic in 50 design colours. Green product for bio-building.

