


TILING TO LOW PROFILE HEATING PANELS

- Guarantees safe laying
- Optimises heating system performance
- Insensitive to changes in temperature
- Fast completion of work
- System with very low VOC emissions, improves the quality of air and increases the level of health protection for operators

SUBSTRATE

- 1 Timber panel
- 2 Adhesive
- 3 Low profile heating panel

PREPARATION OF SUBSTRATES



Keragrip® Eco

Certified, eco-friendly, water-based adhesion promoter for compact, absorbent and non-absorbent substrates.

Coverage

≈ 0.1 – 0.2 kg/m²

SUBSTRATE LEVELLING




Keratech® Eco Flex

Extra fast-acting, certified, eco-friendly, mineral self-levelling product for the high-performance, high-deformability correction of irregular substrates.

Coverage

≈ 1.6 kg/m² per mm of thickness

TILE LAYING



H40® Advanced


Rapid setting, multipurpose Gel-Adhesive, structural, flexible, thixotropic & fluid. For tiles and stone of all types and formats.

Coverage

Grey ≈ 1.3 kg/m² per mm of thickness

White ≈ 1.2 kg/m² per mm of thickness


GROUTING



Fugabella® Color

Decorative Resina-cemento® (resin-cement) for grouting of ceramic and porcelain tiles, mosaic and natural stone in a 50-colour design range. Green product for bio-building.

EXPANSION JOINTS



Silicone Color

Decorative sealant for tiles and mosaic in 50 design colours. Green product for bio-building.

