


TILING TO WOODEN SUBSTRATES WITH HEATING SYSTEM

- Guarantees safe laying on high-deformation substrates
- Optimises heating system performance
- Insensitive to changes in temperature
- Fast completion of work
- System with very low VOC emissions, improves the quality of air and increases the level of health protection for operators

SUBSTRATE

- 1 Timber panel



Keragrip Eco


Certified, eco-friendly, water-based adhesion promoter for compact, absorbent and non-absorbent substrates.

Coverage

≈ 0.1 – 0.2 kg/m²

- 3 Heating system

SUBSTRATE LEVELLING



Keratech® Eco R30

Certified, extra fast-acting, eco-friendly, mineral self-levelling product for the high-performance, highthickness correction of irregular substrates.

Coverage

≈ 1.8 kg/m² per mm of thickness



TILE LAYING



H40® Advanced

Rapid setting, multipurpose Gel-Adhesive, structural, flexible, thixotropic & fluid. For tiles and stone of all types and formats.

Coverage

Grey ≈ 1.3 kg/m² per mm of thickness

White ≈ 1.2 kg/m² per mm of thickness

GROUTING



Fugabella® Colour

Decorative Resina-cemento® (resin-cement) for grouting of ceramic and porcelain tiles, mosaic and natural stone in a 50-colour design range. Green product for bio-building.

EXPANSION JOINTS



Silicone Colour

Decorative sealant for tiles and mosaic in 50 design colours. Green product for bio-building.