

Material: **Ceramic** | Appearance: **Uniform** | Application: **Walls**

8 Colour
2 Finishes
1 Tile size

Ashton

Ashton present pastel and rich vibrant colours, artisan finishes, trendy metallics and earthy tones in a 3D geometric form. Ashton is suitable for internal wall applications.



Shade variation: V1 - Uniform



Matt



OOBC51522T1

Gloss



OOBC51523T1

Metallic



OOBC51527T1



OOBC51525T1

Mix - Fifteen different colours randomly mixed within the box.



OOBC51529T1

	SIZES (mm)	> <	FINISHES		
1	100x250	8-14mm	MATT	GLOSS	METALLIC

1



LRV and PTV values can vary batch to batch, please contact for advice. Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:

Material: **Ceramic** | Appearance: **Uniform** | Application: **Walls**



Ashton



LRV and PTV values can vary batch to batch, please contact for advice.
Switch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:    



Ashton

Technical data sheet - ISO 10545 average values

3	Water absorption	Eb>10%
4	Breaking strength	Thickness $\geq 7,5$ mm min 12 N/mm ² Thickness < 7,5 mm min 15 N/mm ²
11	Crazing resistance	Pass (Except OOB51528T1)
13	Chemical resistance	GHA (Except OOB51528T1)
14	Stain resistance	Class 5

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Cloth

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Important information - Metallic tiles *

The special metallic glaze of these tiles is particularly acid-sensitive. Anti-limescale products should not be used for ordinary maintenance. We recommend to use a natural cleaner such as Fila Cleaner. Do not use aggressive cleaning products such as bleach or ammonia.

Complaints due to a laying or fixing mistakes will not be accepted.

Please see www.filasolutions.com for methods of use, dilution and coverage

Please see www.filasolutions.com for methods of use, dilution and coverage.