

Material: **Ceramic** | Appearance: **Uniform** | Application: **Walls**

24 Colours
4 Finishes
1 Tile size

Kos

Kos offers an expansive range of coloured bevelled tiles, suitable for internal wall applications.



Shade variation: V1 uniform



Gloss



AWC9051 LRV: 78 AWC9056 LRV: 67 AWC38166 AWC9645 LRV: 50 AWC9644 LRV: 27 AWC9058 LRV: 4 AWC9642 LRV: 29




AWC9641 LRV: 0 AWC9643 LRV: 6 AWC9646 LRV: 1 AWC38167 AWC9059 LRV: 0 AWC9099 LRV: 0 AWC9057 LRV: 0



AWC9098 LRV: 16

Crackle



AWC38124 LRV: 63 AWC38125 LRV: 0 AWC38126 LRV: 1 AWC38127 LRV: 0 AWC38128 LRV: 0 AWC9050 LRV: 85 AWC38168

Matt

Metallic



AWC9054 AWC9055



LRV and PTV values can vary batch to batch, please contact for advice.
Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:




Kos



Formats

	Sizes (mm)	> <	AWC 9051	AWC 9056	AWC 38166	AWC 9645	AWC 9644	AWC 9058	AWC 9642	AWC 9641	AWC 9643	AWC 9646	AWC 38167	AWC 9059	AWC 9099	AWC 9057	AWC 38124	AWC 38125	AWC 38126	AWC 38127	AWC 38128	AWC 9050	AWC 38168	AWC 9054	AWC 9055
1	75x150 BEV	10mm	☐	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
2	75x75 Ang	10mm	☐	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
3	10x150 Listello	10mm	☐	■			■	■								■									
4	12x150 Perfil	10mm	☐	■			■	■								■									
5	75x150 Cornisa	10mm	☐	■			■	■								■									
6	25x150 Trenza	10mm	☐	■			■	■								■									
7	50x150 Petalos	10mm	☐	■			■	■								■									
8	25x150 Escocia	10mm	☐	■			■	■								■									
9	25x150 Cubrecanto	10mm	☐	■			■	■								■									
10	150x150 Zocalo	10mm	☐	■			■	■								■									
11	20x150 Ang Zocalo	10mm	☐	■			■	■								■									
12	50x150 Moldura	10mm	☐	■			■	■								■									
13	30x50 Ang Moldura	10mm	☐	■			■	■								■									





Kos

Technical data sheet - ISO 10545 average values

3	Water absorption	16-16%
11	Crazing resistance	Qualified
13	Chemical resistance	Class GHA
14	Stain resistance	Class 5

Important information - Metallic tiles

The special metallic glaze of these tiles is particularly acid-sensitive. Anti-limescale products should not be used for ordinary maintenance. We recommend to use a natural cleaner such as Fila Cleaner.

Do not use aggressive cleaning products such as bleach or ammonia.

Complaints due to a laying or fixing mistakes will not be accepted.

Sustainability information



Cleaning and maintenance advice

Before grouting *crackle tiles

A pre grout protector Fila PRW200 is advised to protect the tiles; this is a temporary seal that when cleaning the grout will wash off.

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Cloth

Impregnating *crackle tiles

It is also recommended to seal the body of the crackle effect tiles with Fila MP90.

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.