

Material: **Porcelain** | Appearance: **Wood effect** | Application: **Walls and floors**

4

3

2

Colours
Finishes
Tile sizes

Lumber Hi-Tech One

Timber effect porcelain tiles suitable for wall and floor applications, indoors and outdoors.



Shade variation: V3 - High



PERT42340



PERT42342



PERT42343
PERT42343THK*



PERT42344



| | Sizes (mm) | > < | Finishes | |
|---|--------------|------|-------------------|------------|
| 1 | 400x1200 THK | 20mm | - | THK R11/C* |
| 2 | 200x1200 | 10mm | NAT R10 ≥36 PTV | AS R11/C - |



LRV and PTV values can vary batch to batch, please contact for advice. Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:



Lumber Hi-Tech One



Above
Floor: PERT42340



Above
Floor: PERT42343



Lumber Hi-Tech One

Technical data sheet - ISO 10545 average values

| | | |
|----|---|---|
| 2 | Sizes | Conforms |
| 3 | Water absorption | < 0,1 % |
| 4 | Bending strength | > 2500 N > 45 N/mm² |
| 8 | Coefficient of linear thermal expansion | < 9 (MK-1) |
| 9 | Thermal shock resistance | Resistant |
| 12 | Frost resistance | Resistant |
| 13 | Chemical resistance | Class A |
| 14 | Stain resistance | Class 5 |
| | Slip resistance | NAT R10 ≥36 PTV AS R11/C THK R11/C |
| | Recycled content | 10mm thick - 19% 20mm thick - 15% |

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.