

Material: **Ceramic** | Appearance: **Uniform** | Application: **Walls**

16 Colours 3 Finishes 3 Tile sizes


Cesano Metro

Cesano Metro offers a vibrant assortment of metro-shaped wall tiles, available in a flat or beveled style.



Shade variation: V1 uniform

Matt



YC5311 LRV: 80 YC5309 LRV: 9 YC5312 LRV: 4 YC5461 LRV: 43 YC5466 LRV: 46 YC5460 LRV: 58

Gloss



YCG5361 LRV: 73 YCG5364 LRV: 26 YCG5458 YCG5362 LRV: 0 YCG5481 LRV: 8 YCG5482 LRV: 10



YCG5365 LRV: 66 YCG5372 LRV: 2

Metallic *



YC5359 YC5360



LRV and PTV values can vary batch to batch, please contact for advice. Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:



Cesano Metro



Cesano Metro YC5312

Formats

	Sizes (mm)	> <	YC5311	YC5309	YC5312	YC5461	YC5466	YC5460	YCG5361	YCG5364	YCG5458	YCG5362	YCG5481	YCG5482	YCG5365	YCG5372	YC5360	YC5359
1	75x150 FLAT	6.5mm							□	■	■	■	■	■	■	■		
2	75x150 BEV	9mm	□	■	■	■	■	■	□	■	■	■	■	■	■	■	■	■
3	75x75 BEV	9mm	□	■	■	■	■	■	□	■	■	■	■	■	■	■		
4	FINALE 50x150	6.5mm	□	■					□	■	■	■	■	■	■	■		
5	ANG INTERNO FINALE	6.5mm	□	■					□	■	■	■	■	■	■	■		
6	ANG ESTERNO FINALE	6.5mm	□	■					□	■	■	■	■	■	■	■		
7	BATTISCOPIA 150x150	6.5mm	□	■					□	■	■	■	■	■	■	■		
8	ANG INTERNO SK	6.5mm	□	■					□	■	■	■	■	■	■	■		
9	ANG ESTERNO SK	6.5mm	□	■					□	■	■	■	■	■	■	■		
10	CANALETTA INTERNA 30x150	6.5mm	□	■					□	■	■	■	■	■	■	■		
11	CANALETTA ESTERNA 30x150	6.5mm	□	■					□	■	■	■	■	■	■	■		





Cesano

Technical data sheet - ISO 10545 average values

2	Sizes	Conforms
3	Water absorption	Conforms
4	Bending strength	30-50N/mm ²
8	Coefficient of linear thermal expansion	<7MK-1
9	Resistance to thermal shock	Conforms
12	Frost resistance	Conforms
13	Chemical resistance	Conforms

* Important information - Metallic tiles YC5359 YC5360

The special metallic glaze of these tiles is particularly acid-sensitive. Anti-limescale products should not be used for ordinary maintenance. We recommend to use a natural cleaner such as Fila Cleaner.

Do not use aggressive cleaning products such as bleach or ammonia.

Complaints due to a laying or fixing mistakes will not be accepted.

LRV and PTV values can vary batch to batch, please contact for advice.
Swatch colours may vary, samples should be requested.

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Cloth

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.