

Material: **Porcelain** | Appearance: **Stone effect** | Application: **Walls and floors**

5

1

3

Colours      Finish      Tile sizes

# Ceppo Fleck


The Ceppo Fleck tile collection offers the elegance of ceppo stone in five porcelain stoneware colours. Available in three formats, these tiles feature a natural slip rating of over 36 PTV, ensuring both style and safety. Perfect for any space, Ceppo Fleck combines beauty and durability seamlessly.



Shade variation: V2 moderate



RBEB55209      RBEB55210      RBEB55211      RBEB55212      RBEB55213



	Sizes (mm)	>  <	Finishes
1	600x1200	8.5mm	NAT R10 ≥40 PTV
2	600x600	8.5mm	NAT R10 ≥40 PTV
3	300x600	8.5mm	NAT R10 ≥40 PTV



Ceppo Fleck RBEB55213



LRV and PTV values can vary batch to batch, please contact for advice. PTV values refer to Slider 96 (shod) – Wet (unless stated). Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:

Material: **Porcelain** | Appearance: **Stone effect** | Application: **Walls and floors**



# Ceppo Fleck



Above  
Ceppo Fleck RBEB55210

Right  
Ceppo Fleck RBEB55212



Above  
Ceppo Fleck RBEB55209

LRV and PTV values can vary batch to batch, please contact for advice.  
Swatch colours may vary, samples should be requested.

[www.grestec.co.uk](http://www.grestec.co.uk) | T: 0345 130 2241 | E: [sales@grestec.co.uk](mailto:sales@grestec.co.uk)

Find us on:    



# Ceppo Fleck

## Technical data sheet - ISO 10545 average values

2	Sizes	Conforms
3	Water absorption	<0.1%
4	Modulus of rupture	>45 N/mm <sup>2</sup>
4	Breaking strength (S)	Conforms
8	Linear thermal expansion	as 7-10-6 °C-1
9	Thermal shock resistance	Resistant
12	Frost resistance	Resistant
13	Chemical resistance	LA HA
14	Stain resistance	Class 5
	Slip resistance DIN 51130/ DIN 51097	NAT R10
	Pendulum test (Shod) - Slider 96	NAT ≥40PTV

## Sustainability information



### Cleaning and maintenance advice

#### Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.  
Product: Deterdek Pro

#### Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.  
Product: Cleaner Pro

#### Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.  
Product: PS/87 Pro

Please see [www.filasolutions.com](http://www.filasolutions.com) for methods of use, dilution and coverage.