





Ceppo Fleck

The Ceppo Fleck tile collection offers the elegance of ceppo stone in five porcelain stoneware colours. Available in three formats, these tiles feature a natural slip rating of over 36 PTV, ensuring both style and safety. Perfect for any space, Ceppo Fleck combines beauty and durability seamlessly.















Shade variation: V2 moderate



RBEB55209

RBEB55210

RBEB55211

RBEB55212

RBEB55213

2



Sizes (mm)		> < Finishes	
1	600x600	8.5mm	NAT R10 ≥40 PTV
2	300x600	8.5mm	NAT R10 ≥40 PTV





Ceppo Fleck



Above Ceppo Fleck RBEB55210

Right Ceppo Fleck RBEB55212





Above Ceppo Fleck RBEB55209



Ceppo Fleck

Technical data sheet - ISO 10545 average values

2	Sizes	Conforms	Berindh Ausenment Burkan UKAS MAMACAMENT VERIFIED
3	Water absorption	<0.1%	ISO 14001 ENVIRONMENTAL MANAGEMENT
4	Modulus of rupture	>45 N/mm2	Cleaning and maintenance
4	Breaking strength (S)	Conforms	Initial washing The initial washing is fundan
8	Linear thermal expansion	a≤ 7·10-6 °C-1	any laying residues and buil Product: Deterdek Pro
9	Thermal shock resistance	Resistant	Routine maintenance The aim of the routine main Product: Cleaner Pro
12	Frost resistance	Resistant	Special maintenance Special maintenance is carr
13	Chemial resistance	LA HA	enough to restore the origin Product: PS/87 Pro
14	Stain resistance	Class 5	Please see www.filasolution
	Slip resistance DIN 51130/ DIN 51097	NAT R10	
	Pendulum test (Shod) - Slider 96	NAT≥40PTV	

Sustainability information



ce advice

amental for good treatment results. The initial washing is aimed at removing uilding grime.

intenance is to remove dirt and scuff marks. Must be carried out regularly.

arried out in case of very stubborn dirt, when the routine maintenance is not ginal look of the surface.

ons.com for methods of use, dilution and coverage.