


Material: **Porcelain** | Appearance: **Scored mosaic** | Application: **Walls and floor**

Abaculus

Abaculus is a 50x50mm mosaic tile designed with architects and interior designers in mind, featuring an 8x8mm scored mosaic effect and a refined patterned textured relief. Ideal for internal wall and floor applications, it delivers a sophisticated blend of form and function. With 18% recycled content, Abaculus supports sustainable design without sacrificing aesthetic or performance integrity.



Shade variation: V2 moderate




TSB32185
LRV: 76




TSB32186
LRV: 28



TSB32187
LRV: 4




TSB32188
LRV: 5



TSB32189
LRV: 20

50x50 mosaic with 8x8 scored mosaic effect supplied on 316x316 mesh sheet

1



	Sizes (mm)	> <	Finishes
1	50x50 MOS WITH SCORED 8x8 MOS on 316x316 MESH	5mm	Matt R10 ≥36PTV

LRV and PTV values can vary batch to batch, please contact for advice. PTV values refer to Slider 96 (shod) – Wet (unless stated). Swatch colours may vary, samples should be requested.

Find us on:



Abaculus TSB32188



www.grestec.co.uk | T: +44 (0)345 130 2241 | E: sales@grestec.co.uk

Material: **Porcelain** | Appearance: **Scored mosaic** | Application: **Walls and floor**



Abaculus



Above
Abaculus TSB32185

Right
Abaculus TSB32188



Above
Abaculus TSB32186

LRV and PTV values can vary batch to batch, please contact for advice. PTV values refer to Slider 96 (shod) – Wet (unless stated). Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:   



Abaculus

Technical data sheet - ISO 10545 average values

3	Water absorption	Conforms
6	Resistance to deep abrasion	<140mm ³
8	Linear thermal expansion	<9 (MK)-1
9	Thermal shock resistance	Resistant
12	Frost resistance	Resistant
13	Chemical resistance	GLA to GLB
14	Stain resistance	Class 5
	Slip resistance	Matt R10
	Pendulum test - Slider 96 (Shod) Wet	Matt ≥36PTV

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.