

Material: **Glazed porcelain** | Appearance: **Handcrafted** | Application: **Walls**

8

Colours

1

Finish

1


Tile size

Arko

Drawing inspiration from the Mojave Desert, the Arko collection interprets its rich tonal palette through a compact 60x250Mm ceramic format, specifically engineered for wall installations. Available in eight carefully curated colourways, each tile showcases a subtly uneven glazed finish, achieved through advanced surface treatment processes that replicate the weathered appearance caused by prolonged exposure to natural elements.



Shade variation: V3 high (White V1)



RBDC53892



RBDC53893




RBDC53894



RBDC53895



RBDC53896



RBDC53897



RBDC53898



RBDC53899

1



Size (mm)	Thickness	Finish
1 60x250	9,5	Gloss



LRV and PTV values can vary batch to batch, please contact for advice. PTV values refer to Slider 96 (shod) – Wet (unless stated). Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:



Arko

Technical data sheet - ISO 10545 average values

3	Water absorption	$\leq 0,5\%$
4	Bending Strength	$R \geq 35 \text{ N / mm}^2$ $S > 700 \text{ N (spessore < 7,5 mm)}$ $S > 1300 \text{ N (spessore} \geq 7,5 \text{ mm)}$
14	Stain resistance	Class 3
6	Deep abrasion resistance	$\leq 175 \text{ mm}^3$
	Hardness in Mohs degrees	$\geq 5^\circ \text{ Mohs}$

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.
Product: Cloth

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.
Product: Cleaner Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.