





Arko

Drawing inspiration from the Mojave Desert, the Arko collection interprets its rich tonal palette through a compact 6x25 cm ceramic format, specifically engineered for wall installations. Available in eight carefully curated colourways, each tile showcases a subtly uneven glazed finish, achieved through advanced surface treatment processes that replicate the weathered appearance caused by prolonged exposure to natural elements such as wind and sand.









Shade variation: V3 high (White V1)











RBDC53892





RBDC53896

RBDC53897

RBDC53893

RBDC53898

RBDC53899

RBDC53895



Size (mm)		Thickness	Finish	
1	60v250	0.5	Gloss	





Arko



Above Arko RBDC53892

Right Arko RBDC53894





Above Arko RBDC53899



Arko

Technical data sheet - ISO 10545 average values

3 Water absorption ≤ 0,5%

R ≥ 35 N / mm²
S > 700 N (spessore < 7,5 mm)
S > 1300 N (spessore ≥ 7,5 mm)

14 Stain resistance Class 3

6 Deep abrasion resistance ≤175 mm³

Hardness in Mohs degrees ≥ 5° Mohs

Sustainability information







Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Cloth

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly. Product: Cleaner Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.