

Material: **Ceramic** | Appearance: **Embossed** | Application: **Walls**

48

Colours

1

Finishes

2

Tile sizes

Regenta


















Regenta delivers a high-performance solution for the vertical plane, where sculptural dimensionality meets a refined glaze. This series centers on a rhythmic interplay of light and shadow, driven by signature three-dimensional profiles - T1 and T2. Whether utilising the soft, organic arcs or the sharp, geometric reliefs, Regenta transforms static walls into dynamic, light-catching installations.







3D + Flat 125×250mm

											
TTAF52551 LRV: 61	TTAF52551T1	TTAF52551T2	TTAF52552 LRV: 39	TTAF52552T1	TTAF52552T2	TTAF52553 LRV: 9	TTAF52553T1	TTAF52553T2	TTAF52554 LRV: 29	TTAF52554T1	TTAF52554T2
											
TTAF52555 LRV: 15	TTAF52555T1	TTAF52555T2	TTAF52556 LRV: 41	TTAF52556T1	TTAF52556T2						

3D + Flat 58×116 | Flat 116×116mm

											
CAEA50650	CAEA50650T1	CAEA50650T2	CAEA50651	CAEA50651T1	CAEA50651T2	CAEA50652	CAEA50652T1	CAEA50652T2	CAEA50653	CAEA50653T1	CAEA50653T2
											
CAEA50654	CAEA50654T1	CAEA50654T2	CAEA50655	CAEA50655T1	CAEA50655T2	CAEA50656	CAEA50656T1	CAEA50656T2	CAEA50657	CAEA50657T1	CAEA50657T2
											
CAEA50658	CAEA50658T1	CAEA50658T2	CAEA50659	CAEA50659T1	CAEA50659T2						

LRV and PTV values may vary between batches; please contact us for guidance.
 Swatch colours may differ from final production—samples are recommended.
www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk
 Find us on:    





Regenta

Technical data sheet - ISO 10545 average values

<p>2 Sizes</p> <p>3 Water absorption</p> <p>4 Modulus of rupture Breaking strength</p> <p>7 Abrasion resistance</p> <p>8 Linear thermal expansion</p> <p>12 Frost resistance</p> <p>13 Resistance to low concentrations of acids and alkali Resistance to high concentrations of acids and alkali Resistance to domestic chemicals and additives for swimming pools</p> <p>14 Stain resistance</p>	<p>Conforms</p> <p>Conforms</p> <p>Conforms</p> <p>From 3 to 5</p> <p>6 × 10⁻⁶</p> <p>Resistant</p> <p>From GLA to GLB From GHA to GHB GA</p> <p>Class 5</p>
--	---

Sustainability information



Cleaning and maintenance advice

Initial washing
The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.
Product: Cloth

Routine maintenance
The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.
Product: Cleaner Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.

LRV and PTV values may vary between batches; please contact us for guidance.
Swatch colours may differ from final production—samples are recommended.
www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:

