

Material: **Porcelain** | Appearance: **Timber** | Application: **Floors**

4 Colours    1 Finish    1 Tile size

# Linton 20

Linton 20 delivers the natural appeal of timber with the durability of 20mm porcelain, engineered for demanding commercial environments. With a slip-resistant surface and high-strength construction, it's ideal for public spaces, hospitality settings, and high-traffic outdoor areas, offering a reliable, low-maintenance solution with a refined, contemporary finish.



RBFB55281



RBFB55282



RBFB55283



RBFB55284

1



Sizes (mm)	Thickness	PTV Wet Slider 96	PTV Wet Slider 55
1 400x1200	20	Thick $\geq$ 45PTV	Thick $\geq$ 45PTV



Linton 20 RBFB55284

LRV and PTV values may vary between batches; please contact us for guidance. Swatch colours may differ from final production—samples are recommended. [www.grestec.co.uk](http://www.grestec.co.uk) | T: 0345 130 2241 | E: [sales@grestec.co.uk](mailto:sales@grestec.co.uk)  
Find us on:



Material: Porcelain | Appearance: Timber | Application: Floors







# Linton 20



Above  
Linton 20 RBFB55282



Above  
Linton 20 RBFB55284

LRV and PTV values may vary between batches; please contact us for guidance.  
Swatch colours may differ from final production—samples are recommended.  
[www.grestec.co.uk](http://www.grestec.co.uk) | T: 0345 130 2241 | E: [sales@grestec.co.uk](mailto:sales@grestec.co.uk)  
Find us on:    



# Linton 20

## Technical data sheet - ISO 10545 average values

3	Water absorption	< 0,1%
4	Breaking strength	> 45 N/mm <sup>2</sup>
12	Frost resistance	Resistant
14	Stain resistance	Class 5
	Pendulum test - Slider 96 (Shod) Wet	Thick ≥45PTV
	Pendulum test - Slider 55 (Barefoot) Wet	Thick ≥45PTV

## Sustainability information



### Cleaning and maintenance advice

#### Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

#### Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

#### Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see [www.filasolutions.com](http://www.filasolutions.com) for methods of use, dilution and coverage.

LRV and PTV values may vary between batches; please contact us for guidance. Swatch colours may differ from final production—samples are recommended.

[www.grestec.co.uk](http://www.grestec.co.uk) | T: 0345 130 2241 | E: [sales@grestec.co.uk](mailto:sales@grestec.co.uk)

Find us on: