

Material: Porcelain | Appearance: Timber | Application: Walls and floors

6
Colours







2
Finish

5
Tile sizes



Nash 2.0

Nash 2.0 is a contemporary wood-look tile collection that captures the natural warmth and texture of timber with the durability of porcelain. Featuring soft grain patterns and versatile tones, it creates calm, elegant spaces suited to both residential and commercial interiors.




		
RBFC55285 LRV 37	RBFC55286 LRV 32	RBFC55287 LRV 27
		
RBFC55288 LRV 27	RBFC55289 LRV 29	RBFC55290 LRV 24



Sizes (mm)	Thickness	 PTV Wet Slider 96	 PTV Wet Slider 55	Availability
1 400x1200	20	Thick ≥ 45 PTV	Thick ≥ 45 PTV	RBFC55289, 90
2 240x1500	8.5	Natural ≥ 40 PTV	Natural ≥ 38 PTV	All colours
3 234x1480	8.5	Natural ≥ 40 PTV	Natural ≥ 38 PTV	All colours
4 200x1200	8.5	Natural ≥ 40 PTV	Natural ≥ 38 PTV	All colours
5 200x1200 T1	8.5	Natural ≥ 40 PTV	Natural ≥ 38 PTV	All colours



Nash 2.0 RBFC55289

LRV and PTV values may vary between batches; please contact us for guidance. Swatch colours may differ from final production—samples are recommended.
www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk
 Find us on: 



Material: Porcelain | Appearance: Timber | Application: Walls and floors



Nash 2.0







Above
Nash 2.0 RBFC55288

Right
Nash 2.0 RBFC55290



Above
Nash 2.0 RBFC55287

LRV and PTV values may vary between batches; please contact us for guidance.
Swatch colours may differ from final production—samples are recommended.
www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:    



Nash 2.0

Technical data sheet - ISO 10545 average values

3	Water absorption	< 0,1%
4	Breaking strength	> 45 N/mm ²
12	Frost resistance	Resistant
14	Stain resistance	Class 5
	Pendulum test - Slider 96 (Shod) Wet	Natural ≥40 PTV Thick ≥45PTV
	Pendulum test - Slider 55 (Barefoot) Wet	Natural ≥38 PTV Thick ≥45PTV

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.

LRV and PTV values may vary between batches; please contact us for guidance.
Swatch colours may differ from final production—samples are recommended.
www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on: