

Material: **Porcelain** | Appearance: **Timber** | Application: **Walls and floors**

3
Colours

2
Finish

5
Tile sizes

Nash 3.0

Nash 3.0 is a vintage wood-look tile collection that captures the natural warmth and texture of timber with the durability of porcelain. Featuring soft grain patterns and versatile tones, it creates calm, elegant spaces suited to both residential and commercial interiors.



RBFD55291
LRV 38

RBFD55292
LRV 36

RBFD55293
LRV 28



Sizes (mm)	Thickness	PTV Wet Slider 96	PTV Wet Slider 55	Availability
1 400x1200	20	Thick \geq 45PTV	Thick \geq 45PTV	RBFD55292, 93
2 240x1500	8.5	Natural \geq 36PTV	Natural 25-35 PTV	All colours
3 234x1480	8.5	Natural \geq 36PTV	Natural 25-35 PTV	All colours
4 200x1200	8.5	Natural \geq 36PTV	Natural 25-35 PTV	All colours
5 200x1200 T1	8.5	Natural \geq 36PTV	Natural 25-35 PTV	All colours



Nash 3.0 RBFD55292

LRV and PTV values may vary between batches; please contact us for guidance.
 Swatch colours may differ from final production—samples are recommended.
www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk
 Find us on:



Material: Porcelain | Appearance: Timber | Application: Walls and floors



Nash 3.0







Above
Nash 3.0 RBF5291

Right
Nash 3.0 RBF5292



Above
Nash 3.0 RBF5293

LRV and PTV values may vary between batches; please contact us for guidance.
Swatch colours may differ from final production—samples are recommended.
www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:    



Nash 3.0

Technical data sheet - ISO 10545 average values

3	Water absorption	< 0,1%
4	Breaking strength	> 45 N/mm ²
12	Frost resistance	Resistant
14	Stain resistance	Class 5
	Pendulum test - Slider 96 (Shod) Wet	Natural ≥36PTV Thick ≥45PTV
	Pendulum test - Slider 55 (Barefoot) Wet	Natural 25-35 PTV Thick ≥45PTV

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.

LRV and PTV values may vary between batches; please contact us for guidance.
Swatch colours may differ from final production—samples are recommended.
www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on: