

Svale

3 Colours | 1 Finish | 1 Size

Svale brings the warm, organic aesthetic of natural timber into high-traffic commercial and residential environments. Combining realistic graining with the durability of porcelain, Svale provides a versatile floor and wall solution that requires minimal maintenance while delivering modern warmth to modern interiors.



LKAE52270



LKAE52271



LKAE52272



Svale

1

2

3

Size (mm)		Thickness		
1	300×1500	10	Ultra Matt ≥40PTV	Ultra Matt 25-35PTV
2	230×1200	9.7	Ultra Matt ≥40PTV	Ultra Matt 25-35PTV
3	150×900	8.5	Ultra Matt ≥40PTV	Ultra Matt 25-35PTV



ISO 10545 Results

3	Water absorption	$Ev \leq 0,5\%$
4	Bending strength	$>1300 \text{ N}$
4	Modulus of rupture	$N \geq 35 \text{ N/mm}^2$

Slip resistance

Pendulum test - Slider 96 (Shod) Wet	Ultra Matt $\geq 40\text{PTV}$
Pendulum test - Slider 55 (Barefoot) Wet	Ultra Matt 25-35PTV

Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.

LRVs and PTVs

LRV and PTV values may vary between batches; please contact us for guidance.

Document + web colours

Swatch colours may differ from final production, samples are recommended.

Sustainability



Shade variation

